

Traffic Control Plan - Cold Mill and Paving - Lowen Paving - August 2nd



Streetwise
TRAFFIC CONTROLLERS™
TRAFFIC PLAN

DATE OF LAST REVISION
2016-07-29

Contractor Name: **Lowen Paving**
Job Description: **Cold Mill and Paving
9473 Broadway Street**

Traffic Supervisor Contact: **Angelia Fox** Phone: **604-858-7730** Email: **Angelia@StreetwiseTraffic.ca**

Traffic Plan Contact: **Tehjay Fox** Phone: **604-799-6750** Email: **Tehjay@StreetwiseTraffic.ca**

Date: **August 2nd, 2016**

TCP # **TCP 1 of 1**

LEGEND

- TRAFFIC CONTROL PERSONNEL
- TUBULAR MARKER - TYPE D
- SIGN STAND (TRIPOD)
- BUFFER VEHICLE
- SIGN STAND (WINDMASTER)
- FLASHING ARROW BOARD (FAB)
- EXISTING BUS STOP CLOSED
- SIGN FLAGS
- CLASS 1 BARRICADE
- RELOCATED BUS STOP
- WORKZONE

- DRAWING SPECIFIC NOTES**
- All traffic control shall conform to the TCM and the latest catalogue for Standard Traffic Signs
 - Signs shown are representations of signs only and the MOTI Construction Sign Catalogue should be used for detailed sign design
 - Signs shown are in meters and are the minimum except as otherwise indicated
 - All personnel shall be trained in the use of traffic control devices and will be in effect
 - Active Work Zones and Hazards shall be delineated to protect workers and the traveling public
 - Maximum distance between cones/delineator/barrel should be 10m
 - Tubular markers and signs will be double based and well secured during windy conditions
 - Dimensions are indicated due to urban block length
 - These pages are best printed on a tablet (11x17) page size

- GENERAL NOTES**
- All traffic control shall conform to the TCM and the latest catalogue for Standard Traffic Signs
 - Signs shown are representations of signs only and the MOTI Construction Sign Catalogue should be used for detailed sign design
 - Signs shown are in meters and are the minimum except as otherwise indicated
 - All personnel shall be trained in the use of traffic control devices and will be in effect
 - Active Work Zones and Hazards shall be delineated to protect workers and the traveling public
 - Maximum distance between cones/delineator/barrel should be 10m
 - Tubular markers and signs will be double based and well secured during windy conditions
 - Dimensions are indicated due to urban block length
 - These pages are best printed on a tablet (11x17) page size