



Streetwise TRAFFIC CONTROLLERS INC. TRAFFIC PLAN	Contractor Name: Element Excavating	SHEET # Sheet 1 of 1	Date: September 26th to 28th
TRAFFIC CONTROL PLAN DATE OF LAST REVISION 2016-09-21	Job Description: Underground Telus and Shaw Connections	Contractor Contact: Les Klaskan Phone: 604-796-0041	Traffic Supervisor Contact: Angelia Fox Phone: 604-858-7730
		Traffic Plan Contact: Tehjay Fox Phone: 604-799-6750	Email: Angelia@StreetwiseTraffic.ca
			Email: Tehjay@StreetwiseTraffic.ca

LEGEND	
	TRAFFIC CONTROL PERSONNEL
	SIGN STAND (TRIPOD)
	SIGN STAND (WINDMASTER)
	SIGN FLAGS
	CLASS 1 BARRICADE
	WORKZONE
	TRAFFIC BARREL
	TUBULAR MARKER - TYPE D
	TRAFFIC CONTROL VEHICLE
	FLASHING ARROW BOARD (FAB)
	EXISTING BUS STOP CLOSED
	RELOCATED BUS STOP

DRAWING SPECIFIC NOTES

- Signs shown are representations of signs only and the MOTT Construction Sign Catalogue should be used for detailed sign design
- Dimensions shown are in meters and are the minimums except as otherwise indicated
- All signs shall be placed in advance of the work zone and shall be removed when the work zone is closed
- Active Work Zones and Hazards shall be delineated for the work zone and the travelling public
- Maximum distance between cones/barricade should be 10m
- Tubular markers and signs will be double based and well secured during windy conditions
- All signs shall be placed on the side of the road to be closed
- These pages are best printed on a tabloid (11x17) page size

GENERAL NOTES

- All traffic control shall conform to the TCM and the latest catalogue for Standard Traffic Signs
- Signs shown are representations of signs only and the MOTT Construction Sign Catalogue should be used for detailed sign design
- Dimensions shown are in meters and are the minimums except as otherwise indicated
- All signs shall be placed in advance of the work zone and shall be removed when the work zone is closed
- Active Work Zones and Hazards shall be delineated for the work zone and the travelling public
- Maximum distance between cones/barricade should be 10m
- Tubular markers and signs will be double based and well secured during windy conditions
- All signs shall be placed on the side of the road to be closed
- These pages are best printed on a tabloid (11x17) page size