


Regulatory Speed Limit	50 km/h	60 km/h	70 km/h	80 km/h	90-100 km/h
Taper Length For Lane Closure	35 (1:10)	55 (1:25)	75 (1:20)	90 (1:25)	110 (1:50)
Taper Length For Where TCPs Located (Min. 3 Cones)	5	8	10	12	15
Maximum Distance Between Cones or Marker for 1a	10	10	10	10	10
Minimum Tangent Distance Between Tapers	30	60	90	120	150
Distance Between Construction Signs	40	60	80	100	150

**LEGENDS:**

- SIGN STAND
- DELINEATORS
- TCP
- ARROWBOARD TRUCK
- POLE
- REMOVE POLE
- MANHOLE/SERVICE BOX
- NEW AERIAL CABLE
- NEW U/G CABLE

**COMPANY:** DIXON NETWORKS CORPORATION  
**CONTACT:** JOHNNY WOO  
**PHONE:** 604-940-8817 EXT. 238



PG 2

**NOTES:**

- ALL TRAFFIC CONTROL DEVICES AND SIGNS TO COMPLY WITH LATEST MOTH MANUAL WORK ON ROADWAY.
- MAINTAIN MINIMUM 3.2m LANE WIDTH
- NOTIFY CMBC FOR CONSTRUCTION

**SCOPE:** - FIBRE OPTIC CABLE SPLICING

**DATES:** - TBD

**HOURS:** - 7AM - 5PM

**DRAWING #:** - SHAW - RPN 448493 - VA221