


Version 2.0.1 ©2016 Data accuracy not guaranteed

Regulatory Speed Limit	50 km/h	60 km/h	70 km/h	80 km/h	90-100 km/h
Taper Length For Lane Closure	35 (1130)	55 (1215)	75 (1220)	90 (1225)	110 (1330)
Taper Length For Shoulder Work on Where TCPs Used (Min. 3 Cones)	5	8	10	12	15
Minimum Distance Between Cones or Tubular Markers for 1a	10	10	10	10	10
Minimum Tangent Distance Between Tapers	30	60	90	120	150
Distance Between Construction Signs	40	60	80	100	150

LEGENDS:

- SIGN STAND
- DELINEATORS
- TCP
- ARROWBOARD TRUCK
- POLE
- REMOVE POLE
- MANHOLE/SERVICE BOX
- NEW AERIAL CABLE
- NEW U/G CABLE



NOTES:

- ALL TRAFFIC CONTROL DEVICES AND SIGNS TO COMPLY WITH LATEST MOTH MANUAL WORK ON ROADWAY.
- MAINTAIN MINIMUM 3.2m LANE WIDTH
- NOTIFY CMBC FOR CONSTRUCTION

SCOPE: FIBRE OPTIC CABLE SPLICING

DATES: TBD

HOURS: 7AM - 5PM

DRAWING #: SHAW - RPN 448493 - VAXXX

COMPANY: DIXON NETWORKS CORPORATION
CONTACT: JOHNNY WOO
PHONE: 604-940-8817 EXT. 238

