

© 2016 Data accuracy not guaranteed

SCOPE:
- FIBRE OPTIC CABLE SPLICING


DATES:
- TBD

HOURS:
- 7AM - 5PM

DRAWING #:
- SHAW - RPN 448493 - VA642

NOTES:

- ALL TRAFFIC CONTROL DEVICES AND SIGNS TO COMPLY WITH LATEST MOTH MANUAL WORK ON ROADWAY.
- MAINTAIN MINIMUM 3.2m LANE WIDTH
- NOTIFY CMBC FOR CONSTRUCTION



	Regulatory Speed Limit	50 km/h	60 km/h	70 km/h	80 km/h	90-100 km/h
1a	Taper Length For Lane Closure (1:10)	35 (1:15)	55 (1:20)	75 (1:25)	90 (1:25)	110 (1:30)
1b	Taper Length For Shoulder Work on Where TCs Used (Min. 3 Cones)	5	8	10	10	15
2	Maximum Distance Between Cones or Tubular Markers for 2a	10	10	10	10	10
3	Minimum Tangent Distance between Tapers	30	60	90	120	150
4	Distance Between Connection Signs	40	60	80	100	150

LEGENDS:

- SIGN STAND
- DELINEATORS
- TCP
- ARROWBOARD TRUCK
- POLE
- REMOVE POLE
- MANHOLE/SERVICE BOX
- NEW AERIAL CABLE
- NEW U/G CABLE

COMPANY: DIXON NETWORKS CORPORATION

CONTACT: JOHNNY WOO
PHONE: 604-940-8817 EXT. 238