



	Regulatory Speed Limit	50 km/h	60 km/h	70 km/h	80 km/h	90-100 km/h
2a	Taper Length For Lane Closure (1:1)	35 (110)	55 (175)	75 (240)	95 (310)	120 (390)
2b	Taper Length For Shoulder Work on Where TCPs Used (Min. 3 Cones)	5	8	10	12	15
2	Minimum Distance Between Cones or Tubular Markers for 2a	10	10	10	10	10
3	Minimum Tangent Distance Between Tapers	30	60	90	120	150
4	Distance Between Construction Signs	40	60	80	100	150

LEGENDS:

- SIGN STAND
- DELINEATORS
- TCP
- ARROWBOARD TRUCK
- POLE
- REMOVE POLE
- MANHOLE/SERVICE BOX
- NEW AERIAL CABLE
- NEW U/G CABLE

COMPANY: DIXON NETWORKS CORPORATION
 CONTACT: JOHNNY WOO
 PHONE: 604-940-8817 EXT. 238

PG5

NOTES:

- ALL TRAFFIC CONTROL DEVICES AND SIGNS TO COMPLY WITH LATEST MOTH MANUAL WORK ON ROADWAY.
- MAINTAIN MINIMUM 3.2m LANE WIDTH
- NOTIFY CMBC FOR CONSTRUCTION

SCOPE: FIBRE OPTIC CABLE SPLICING

DATES: TBD

HOURS: 7AM - 5PM

DRAWING #: SHAW - RPN 448493 - VA203