







- GENERAL NOTES

 *All traffic control shall conform to the TCM and the tatest catalogue for Standard Traffic Signs

 *Signs shown are representations of signs only and the MOTI Constructions Sign Catalogue should be used for detailed sign design

 *Dimensions shown are in meters and are the minimume except as otherwise indicated

 *All permanent signage that will conflict with this sits will be covered or removed while the works are in effect

 *Active Work Zones and Hazards shall be desired to protect workers and the travelling public

 *Maximum distance between condédienteat/Sharter should be 10m

 *Tubular markers and signs will be double based and wet ascured during windy conditions

 *Distances may be adjusted use to urban block length

 *These pages are best printed on a Tabloid (11x17) page size

**









- GENERAL NOTES

 All traffic control shall conform to the TCM and the latest catalogue for Standard Traffic Signs

 Signs shown are representations of signs only and the MOTI Constructions Sign Catalogue should be used for detailed sign design

 Dimensions shown are in meters and are the minimums except as otherwise indicated

 All permanent signage that twil conflict with this sit awill be covered or removed while the works are in effect

 Active Work Zones and Hazards shall be delineated to protect workers and the travelling public

 Advinum distance between concelidenceatro-haret should be to flom

 Tubular markers and signs will be double based and well secured during windy conditions

 Distances may be adjusted due to urban block length

 These pages are best printed on a Tabloid (11x17) page size

e e







DRAWING SPECIFIC NOTES

• Work will be in the parking lane,

• No Parking Signs to be placed 24 to 48 hours in advance,

DIND

- GENERAL NOTES

 All traffic control shall conform to the TCM and the latest catalogue for Standard Traffic Signs

 Signs shown are representations of signs only and the MOTI Constructions Sign Catalogue should be used for detailed sign design

 Dimensions shown are in meters and are the minimums except as otherwise indicated.

 All permanent signage that vall conflict with this sit and the boovered or removed while the works are in effect

 Active Work Zones and Hazards shall be defineated to protect workers and the travelling public

 Advantum distance between concelledineator/haret should be 5 flom

 Tubular markers and signs will be double based and well secured during windy conditions

 Distances may be adjusted due to urban block teigth

 These pages are best printed on a Tabloid (11x17) page size