

	REGULATORY SPEED LIMITS	50 КМ/Н	60 КМ/Н	70 KM/H	80 KM/H	км/н	80 - 110 KM/H(FREEWAY &MULTILANE)		LEGEND					
	TAPER LENGHT FOR LANE CLOSURE	35m (1:10)	55m (1:15)	75m (1:20)	90m (1:25)	110m (1: 30)	165m (1:45)	SYMBOL	SIGN SYMBOL SIGN					
10	TAPER LENGHT FOR SHOULDER WORK OR WHERE TCP® USED	5	8	10	12	15			NUMBER REFERENCE		NUMBER REFERENCE			
2	MAXIMUM DISTANCE BETWEEN CONES OR FOR 1g	10	10	10	10	10	10							
3	MINIMUM TANGENT DISTANCE BETWEEN TAPERS	30	60	90	120	150	200		C-018-1A		DELINEATOF			
4	DISTANCE BETWEEN CONSTRUCTION SIGNS	40	60	80	100	150	200			_				
MENSIONS SHOWN ARE IN METRES AND ARE MINIMUMS EXCEPT FOR 2*. ONES AND TUBULAR MARKERS ARE GENERALLY USED IN DAYLIGHT BUT IF SED AT NIGHT MUST BE REFLECTORIZED. BARRICADES, FLEXIBLE DRUMS OR EMPORARY DELINEATOR POSTS ARE GENERALLY USED DURING HOURS OF ARKNESS AND MUST BE REFLECTORIZED. MENSIONS 1b* APPLY TO DOWNSTREAM TAPERS, SHOULDER TAPERS, AND TO														
ONE SED MP	S AND TUBULAI AT NIGHT MUS ORARY DELINEA (NESS AND MUS	R MARK T BE RI TOR PO T BE RI	ERS ARI EFLECTO STS ARI EFLECTO	e genef Rized. E genef Rized.	RALLY U BARRIC RALLY U	ised in Cades, I Ised Du	DAYLIGHT FLEXIBLE DI RING HOUR	SINGLE LANE TRAFFIC	R-030-8	PREPARE TO STOP	C-029			

	2. SIGNAGE WILL BE TYPICAL FOR EAST & WEST BOUND TRAFFIC & LOCAL TRAFFIC WILL BE GIVEN ACCESS.	PROJECT: CITY OF CHILLIWACK 2016 ASPHALT REHABILITATION & SHOULDER PAVING NEVIN (BETWEEN Ford Road TO McElwee Road)	TITLE: TRAFFIC CONTROL PLAN	DATE	ISSUE/REVISIONS		KEY-WEST ASPHALT (333) LTD. #202-6333 148 St., Surrey, BC Ph: 604-572-0732 Fax: 604-572-0743
--	--	--	--------------------------------	------	-----------------	--	---