



TYSON - STEVENSON SEWER CONNECTION

In order to assist homeowners wishing to connect into the Tyson – Stevenson sewage collection system, the Municipal Development Department has prepared the following list of requirements:

- ✓ All sewer pipe, fittings and glues must be CSA approved for domestic sewer use;
- ✓ All piping to be minimum 100mm (4") in size;
- ✓ A 1% (1/8" per foot) minimum pipe grade must be maintained from the dwelling to the street connection;
- ✓ It is recommended that the piping be kept a minimum of 12" inside all property lines;
- ✓ All piping is to be laid on firm or undisturbed soil and be continuously supported;
- ✓ Any 90° change in direction will require the use of two 45° elbows.
- ✓ Clean outs:
 1. Must be provided in order to permit cleaning of entire system;
 2. One to be installed as close as practical to the outlet at dwelling;
 3. Maximum distance between clean outs is 25.9 meters (85 feet);
 4. Clean outs are to be installed for any change in direction.
- ✓ All installations on private property must meet the BC Building Code;
- ✓ Septic tanks are to be removed or pumped dry and filled with granular material.

***INSPECTION OF THE ABOVE ITEMS WILL BE REQUIRED PRIOR TO ANY BACKFILLING**

For any questions that arise during the planning or installation of your system, please contact the City of Chilliwack Municipal Development Department at 604-793-2905.